

12-21-99

A

## PATENT APPLICATION

12/20/99

ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D. C. 20231Case Docket No. **199-0680**  
Date: December 14, 1999

Sir:

Transmitted herewith for filing is the patent application of Inventor(s):

Vijitha Kiridena

Gregory Smith

Samuel Ebenstein

JCS18 U.S. PTO  
09/467818  
12/20/99For: **VEHICLE DATA ACQUISITION AND DISPLAY ASSEMBLY**

Enclosed are:

- ☒ 4 sheet(s) of drawings  
☒ Assignment and Cover Sheet  
☒ Information Disclosure Statement, PTO Form 1449, and Copies of Citations  
☐ A certified copy of

The filing fee has been calculated as shown below for OTHER THAN A SMALL ENTITY:

FOR	NO. FILED	NO. EXTRA	RATE	SEE
Basic Fee				\$ 760
Total Claims	20	0	18	\$ 0
Indep Claims	3	0	78	\$ 0
Multiple Dependent Claims(s) Presented	0		260	\$ 0
			TOTAL	\$ 760

- [X] Please charge Deposit Account No. 06-1510 in the amount shown next to the Total. A duplicate copy of this sheet is enclosed.
- [X] The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 06-1510. If there are insufficient funds in this account, please charge the fees to Deposit Account No. 06-1500. A duplicate copy of this sheet is enclosed.  
 Any additional filing fees required under 37 CFR 1.16.  
 Any patent application processing fees under 37 CFR 1.17.
- [X] The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 06-1510. If there are insufficient funds in this account, please charge the fees to Deposit Account No. 06-1500.  
 Any patent application processing fees under 37 CFR 1.17.  
 Any filing fees under 37 CFR 1.16 for presentation of extra claims.

"Express Mail"

Mailing Label Number

EL442445766US

Date of Deposit 12-20-99

I hereby certify that this paper or fee is being deposited with the United States Postal Service

"Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patent and Trademarks, Washington, D.C. 20231

Amy Leschan

(Printed Name of Person Mailing Paper or Fee)

Mark L. Mollon

Attorney or Agent of Record  
Registration No. 31,123  
Ford Global Technologies, Inc.  
One Parklane Blvd.,  
600 Parklane Towers East  
Dearborn, MI 48126

**VEHICLE DATA ACQUISITION AND DISPLAY ASSEMBLY****(1) FIELD OF INVENTION**

5       The present invention relates to a vehicle data  
acquisition and display assembly and more particularly,  
to an assembly which selectively acquires and displays  
image type data representing and/or associated with the  
environment or the ambient environment in which a vehicle  
10 resides.

**(2) BACKGROUND OF THE INVENTION**

A typical or conventional vehicle includes one or  
more mirrors which cooperatively provide and/or allow  
15 certain visual images of the environment or ambient  
environment to be acquired and displayed. While these  
mirrors do provide some desired images, the arrangement  
has some drawbacks.

For example and without limitation, the mirrors of a  
20 vehicle do not provide a view of the entire environment  
surrounding the vehicle and therefore substantially  
prevents the driver and/or vehicle occupants from  
acquiring an uninterrupted view of the entire area  
surrounding the vehicle, which is referred to as the  
25 environment or the ambient environment. For example, the  
provided mirror assembly does not typically allow the

driver or the vehicle occupants to view areas and/or regions and/or objects residing within and/or along the left and/or the right frontal portions of the vehicle, especially if the vehicle is travelling behind a relatively large truck or other type of relatively large vehicle, such as a sports utility vehicle. Furthermore, to gain additional environmental image information, drivers are required to undesirably turn or contort their heads, thereby being distracted from the task of driving the vehicle and being forced to "take their eyes off the road". Therefore, it may be desirable to increase the amount of provided environmental image information over that which is provided by the vehicle mirror assemblies and to allow a driver and/or occupants within a vehicle to selectively view the acquired visual or image information representing and/or associated with the environment in which the vehicle resides.

Consequently, there is a need to selectively acquire and display information which represents and/or is associated with the environment in which a vehicle resides, including but not limited to the areas and/or regions which cooperatively surround the vehicle, in a manner which overcomes at least some of the drawbacks associated with prior image acquisition techniques and assemblies.

### SUMMARY OF THE INVENTION

It is a first object of the present invention to provide a data acquisition and display assembly which overcomes some or all of the drawbacks of prior vehicle data acquisition and display assemblies.

It is a second object of the present invention to provide a vehicle data acquisition and display assembly which allows a driver and/or occupant to selectively display certain portions, regions, and/or areas of the environment in which the vehicle resides.

It is a third object of the present invention to provide a vehicle data acquisition and display assembly which selectively provides relatively clean, clear, and "crisp" images of the environment in which the vehicle resides, to a driver of the vehicle and/or to other vehicle occupants.

It is a fourth object of the present invention to provide a vehicle data acquisition and display assembly which selectively displays a view of the environment in which the vehicle resides without requiring the head of the driver of the vehicle to be substantially turned and/or contorted.

According to a first aspect of the present invention, a vehicle data acquisition and display assembly for use with a vehicle which resides within an environment is provided. The assembly comprises at least

one image acquisition apparatus which is disposed upon a vehicle and which acquires images of the environment in which the vehicle resides; a video processing assembly which is coupled to the at least one image acquisition  
5 apparatus, which receives the acquired images, and which uses the acquired images to create a mosaic image of the environment; a display which is coupled to the video processing assembly, which is disposed within the vehicle, and which selectively displays at least one  
10 portion of the mosaic; and an image control assembly which selects the at least one portion, thereby allowing the at least one portion to be selectively displayed by the display assembly.

According to a second aspect of the present  
15 invention, a method for acquiring and selectively displaying images to be viewed within a vehicle is provided. The method comprises the steps of providing a plurality of cameras; disposing the plurality of cameras upon the vehicle, effective to acquire the images;  
20 providing a display; disposing the display within the vehicle, effective to selectively display at least a portion of the plurality of images; generating a voice command; and using the voice command to select the at least a portion of the plurality of images for display.

25 These and other objects, aspects, and advantages of the present invention will become apparent upon reading

the following detailed description of the preferred embodiment of the invention in combination with the accompanying drawings.

5

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a perspective view of a vehicle having and/or employing a data acquisition and display assembly which is made in accordance with the teachings of the preferred embodiment of the invention;

10

Figure 2 is a perspective view of the dashboard portion of the vehicle which is shown in Figure 1;

15

Figure 3 is a block diagram of the data acquisition and display assembly which is made in accordance with the teachings of the preferred embodiment of the invention and which is deployed within the vehicle of Figure 1;

20

Figure 4 is an operational diagram illustrating the creation of a mosaic image by the data acquisition and display assembly which is made in accordance with the teachings of the preferred embodiment of the invention;

Figure 5 is a block diagram of the lens cleaning assembly which is shown in Figure 3;

25

Figure 6 is a perspective view of the dashboard portion of the vehicle which is shown in Figure 1 and which incorporates an image acquisition and display assembly of an alternate embodiment of the invention; and

Figure 7 is a top view of the image control portion of the assembly which is shown in Figure 3.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT OF THE

#### INVENTION

Referring now to Figures 1 and 3, there is shown a data acquisition and display assembly 10 which is made in accordance with the teachings of the preferred embodiment of the invention. As shown, the system 10 includes a camera or image acquisition assembly 15; a vehicle control assembly 20; an image control assembly 25; a voice activated control assembly 30; a video memory assembly 35; an audio assembly 40; a display assembly 45; and a lens cleaning assembly 50 which are each physically, operatively, and communicatively coupled to a "real time" video processing assembly or controller 55 which operates under stored program control. The functionality of each of these portions 15 - 55 of assembly 10 is more fully and completely delineated below.

As shown best in Figure 1, camera assembly 15 includes several image acquisition devices or cameras 75 (i.e., such as and without limitation, six cameras) which are each substantially identical and which are each adapted to be selectively and removably mounted upon the roof 76 of vehicle 60 and to be "aesthetically

integrated" into the "roofline" of the vehicle 60. That is, in the preferred embodiment of the invention, cameras 75 are selectively and equidistantly disposed along at least two edges 78 or the entire perimeter 78 of the roof 76, and have an image acquisition surface or portion 79 which is substantially coplanar to the roof surface portion 81 upon and/or within which they are respectively deployed. It should be appreciated that the substantially coplanar placement of cameras 75 upon roof surface portion 81 substantially protects cameras 75 from damage which may be caused by passing objects and/or other objects and/or debris which may come in close proximity to the vehicle. It should be appreciated that cameras 75 may alternatively be operatively mounted and/or placed upon other portions of the vehicle 60 (e.g., upon the doors).

Cameras 75 cooperatively acquire and provide image data of the environment or the ambient environment 83 that vehicle 60 resides within (i.e., image data of the areas and/or regions and/or objects which cooperatively surround and/or reside within the environment or ambient environment 83 of the vehicle 60). That is, each camera 75 has an operational field of vision or "view" which is generally indicated by arrows 80 and which respectively defines the portions, areas, and/or regions/volumes of the environment or the ambient environment 83 from which



each of the respective cameras 75 may operatively and selectively acquire image data. In the preferred embodiment of the invention, the field of views 80 cooperatively surround the vehicle 60.

5 As shown best in Figure 4, the cameras 75 cooperatively and respectively acquire and provide images 77 from substantially unique areas and/or regions which are included within and/or which form the environment or the ambient environment 83. Particularly, each  
10 respective image 77 represents a different portion or volume of the ambient environment 83. In one non-limiting embodiment of the invention, each field of view 80 of each camera 75 abuts the respective fields of view 80 provided by the two spatially adjacent cameras 75  
15 (i.e., abuts the respective field of view 80 provided by the cameras on each opposed side of the camera 75). In another non-limiting embodiment, each field of view 80 slightly overlaps the fields of view 80 of each of the respectively adjacent cameras 75 (i.e., a portion of the  
20 provided image of a camera 75 is similar to a portion of the image respectively provided by cameras which are adjacent to and which reside on opposite sides of the camera 75). In this manner, the acquired images 77 cooperatively form a panoramic view of the vehicle  
25 environment 83 at the instant of time in which the images 77 are acquired. The image data is stored in memory

assembly 35 in a manner set forth below. In one non-limiting embodiment, these images are "updated" (i.e., newly acquired image data "replaces" the respectively and previously acquired respective image data) at programmed  
5 and/or regular intervals of time (i.e., the newly acquired data is "written over" the previously acquired data within memory 35).

In one non-limiting embodiment of the present invention, the cameras 75 comprise such conventional and  
10 commercially available cameras, such as a "fixed focus" and/or "fixed magnification" type. In a further non-limiting embodiment of the invention, cameras 75 may also comprise conventional "sub-miniature" "CCD" or "CMOS" type video cameras. Furthermore, each of the cameras 75  
15 may, in further non-limiting embodiments, alternatively comprise a conventional and commercially available "color" type, "visible light" type, "infrared", "low light", and/or "image intensifier" type cameras.

Cameras 75, in another alternative embodiment of the  
20 invention, may be selectively dissimilar. Particularly, each camera 75 may operate within a different and/or unique portion of the electromagnetic spectrum (e.g., a conventional and relatively expensive night vision camera may be operatively used to provide images of the portion  
25 of the ambient environment 83 located in the front of the vehicle 60, thereby improving the quality of the image

data of the front of the vehicle which is provided to the driver during foggy or rainy weather, while relatively inexpensive cameras may be deployed on other portions of the vehicle 60). In yet another non-limiting embodiment, 5 imaging wave radar or imaging laser radar type devices and/or assemblies may also be selectively employed to obtain desired image data during adverse weather conditions or to gain visual images associated with objects and/or regions located and/or residing at 10 relatively far distances from vehicle 60.

Each camera 75 is communicatively coupled to a "real time" video processing assembly or controller 55 by use of such media as coaxial cable and/or optical fiber (not shown) and the acquired data and/or images are 15 selectively communicated to the subsystem or assembly 55 by use of this communications media. In the preferred embodiment of the invention, assembly 55 causes certain portions of the acquired image data to be selectively displayed to the driver of vehicle occupants.

20 Vehicle data acquisition and display system 10 further includes a video memory subsystem 35 which selectively receives and records the acquired image data, thereby allowing controller 55 to create a mosaic 85. In one non-limiting embodiment, the video memory subsystem 25 35 comprises conventional random access memory as the storage medium. However, other conventional and/or

commercially available memory devices may alternatively and selectively be used to store the acquired image/visual data including, but not limited to, optical disks, digital tape, and/or analog tape. Once the video memory 35 is "full", previously recorded image data 77 are automatically purged and/or "written over", thereby allowing the newly acquired or "updated" image data 77 to be stored within assembly 10.

As further shown in Figure 4, each acquired image 77 (i.e., the data which respectively forms and/or constitutes and/or is associated with each acquired image 77) is communicated to the video processing assembly 55 and, in one non-limiting embodiment, the processing assembly 55 uses the known orientation and spatial relationship of each of the deployed cameras 75 to selectively create a mosaic or panoramic view 85 of the ambient environment 83. That is, the assembly 55 places each of the acquired images 77 in a certain unique position within the memory assembly 35 based upon the identity (i.e., spatial location upon the roof 76) of the cameras 75 which generated these respective images. By sequentially outputting the previously stored image data in a certain manner, such as and without limitation, by viewing or outputting the images from a first of the cameras 75 and then sequentially viewing or outputting the acquired images from the remaining cameras 75 in the

order that they are positioned upon the vehicle 60 (i.e., in a clockwise fashion) or in some other desired sequence, a "sweep", view, or mosaic 85 of substantially the entire environment or ambient environment 83 may be  
5 obtained. Moreover, a portion of the stored image data may be selectively accessed and displayed, thereby allowing a user to selectively view only a desired singular portion of the ambient environment 83. Mosaic 85 therefore comprises and/or forms a substantially  
10 pictorial and/or visual and relatively seamless "panorama" of the ambient vehicular environment 83.

At least a portion of the created mosaic or seamless panorama 85 is displayed on and/or by the display assembly 45, which is shown in Figures 2 and 4. In one  
15 non-limiting embodiment of the present invention, the display assembly 45 comprises a single flat panel display device and/or apparatus 47 which, in one non-limiting embodiment, is selectively mounted near the center of the instrument panel or dashboard 90 of the vehicle 60. In a  
20 non-limiting embodiment of the invention, display assembly 45 comprises a "heads up" type display or other type of conventional and/or commercially available display system and/or assembly. In further non-limiting  
25 embodiments, the display assembly 45 may alternatively comprise a cathode ray tube; a head mounted display device; a virtual retinal display device; a projection

display device; a holographic display device; a stereoscopic display device; an autostereoscopic display device; and/or a multiple video type display device.

Although the display assembly 45 is shown as an integral part of the dashboard 90 of the vehicle 60, other selective orientations or placements may be utilized. Particularly, as shown best in Figure 6, the display system 45 may alternatively include a display device 47 (e.g., such as a flat panel type display) which "replaces" (e.g., provides substantially identical images as) a conventional rear view mirror 120 and two display devices 50, 52 which are selectively placed upon and/or within dashboard 90 and which respectively and selectively provide images of unique portions of the ambient environment 83 which are substantially and respectively similar to those images provided by conventional vehicle side mirrors (not shown). In this alternative embodiment, display 47 provides a substantially wide angle view of the area and/or region which is located and/or positioned behind the vehicle 60. Devices 50, 52 which may comprise flat panel type displays and selectively provide views or visual information of the areas and/or regions which are located and/or reside behind and along the respective opposite sides of the vehicle 60. The use of such displays 47, 50, 52 allows for sharper, clearer images to be provided

over those respective images provided by conventional vehicle rear-view and side-view mirrors and further substantially prevents, as discussed later, deterioration of the provide images due to adverse weather. The use of devices 50, 52 within the passenger compartment 53 allows the images to be "closer" to the driver and within the driver's field of view, thereby reducing distraction and allowing the driver to quickly and efficiently view the presented images.

10 The assembly 10, in another non-limiting embodiment, allows a user to adjust the view which is selectively displayed by the display assembly 45 through the use of an image control assembly 25. In one non-limiting embodiment, as best shown in Figure 7, the image control  
15 assembly 25 comprises a touch pad assembly 27 which selectively generates and communicates display control commands to the assembly 55 which, when received by the assembly 55, causes certain visual/image data to be presented to the user and/or occupants of the vehicle 60  
20 by use of the display assembly and/or subsystem 45. Particularly, the touch pad assembly 27 comprises an "image choice" controller or touch pad panel member 100 and several selectively depressible switches 105. The touch pad assembly 27 further includes a pictorial  
25 representation or icon 110 of a vehicle, such as and without limitation vehicle 60, which is substantially

positioned in the center of the touch pad panel 100 and several arrows or "quadrant markings" 115 which are positioned upon and which point toward the icon 110 from the periphery 121 of the touch pad panel 100. The

5 markings 115 are substantially and equidistantly disposed around the pictorial representation 110. The touch pad panel 100 operatively resides upon a pressure sensitive electronic signaling device 102 which, in one non-limiting embodiment, is substantially similar to

10 conventional signaling devices which are used within conventional remote controls used by and/or within conventional video game systems and which senses a touch or "press" of a portion of the panel 100 and, in response to such a sensed touch or press, generates and

15 communicates a signal to controller 55.

In operation, when a user touches or presses the panel 100, the electronic signaler 102 produces and communicates a signal to the controller 55 by the use of a bus, cable, or other communication medium (not shown).

20 When received, the generated signal is effective to cause the controller 55 to display a certain portion of the previously created or currently created panoramic view or mosaic 85 upon the display assembly 45. Hence, when a user and/or operator selectively touches the touch pad

25 100, the user may selectively cause certain of the previously acquired images or currently acquired images



77 to be displayed by the display assembly 45, thereby selectively viewing and/or acquiring visual information representing and/or associated with portions of the environment 83 in which the vehicle 60 resides.

5 For example, by touching the front portion 117 of the vehicular representation image icon 110, the previously acquired or currently acquired images of the area and/or region which is disposed and/or positioned in front of the vehicle 60 are selectively displayed upon  
10 display 45. By touching the touch pad 100 to the right or to the left of the schematic vehicle representation 110, previously acquired or currently acquired image data representing and/or associated with respective areas and/or regions which reside to the right of or the left  
15 of vehicle 60 are caused to be selectively displayed by the assembly 45. It should be appreciated that the touch pad 100 may be replaced by other conventional image controllers, including without limitation a conventional joystick, a track ball, or a collection of other types of  
20 selectively arranged switches. It should further be appreciated that images upon displays 47, 50, 52 may be unaltered by touch pad 110.

In another non-limiting embodiment of the invention, the touch pad 100 may also selectively provide "zoom in"  
25 and "pan out" functions. That is, in one non-limiting embodiment, the pad 100 (i.e., portion 102) detects the

distance, proximity, or "how closely" a user is touching the pad 100 in relation to the schematic vehicle representation icon 110 and, based upon such detection, provides the previously acquired or currently acquired

5 images of objects/regions/areas which are "correspondingly" close or far from vehicle 60. That is, if a user touches the pad 100 toward the top quadrant marking 115 which points directly at the front of the schematic vehicle 110, the display subsystem 45 will

10 display "panned out" images or image information associated with objects and/or regions and/or areas which are relatively far away from the front of the vehicle 60 (i.e., objects/regions/areas which reside in the outer most portion of the field of view of that camera 75 which

15 provides information of the front of the vehicle 60). However, should the user touch a point 119 on the touch pad 100 in relative close proximity to the representation 110, the assembly 45 will "zoom" in or selectively display objects and/or regions and/or areas in relative

20 close proximity to the front 117 of the vehicle 60. That is, in one non-limiting embodiment, controller 55 will create a ratio having a numerator equal to the distance 123 from the icon 110 to point 119 and a denominator equal to the distance from the front of the icon 110 to

25 the point 115. This ratio will then be used to select the portion of the previously acquired or currently acquired

images which are to be selected by first identifying the camera 75 which has a field of view 80 which encompasses point 119 and then applying the ratio to the operating length of the field of view 80. The resultant length  
5 determines the "corresponding" portion of the field of view 80 or magnification which is required of the selected camera 75. The portion of the field of view 80 or the appropriate camera magnification will then be used to provide the desired images. Such a ratio may be used  
10 for other selectively touched points upon portion 100.

The touch pad assembly 27 further includes a replay switch assembly 125 and a menu switch assembly 127. In one non-limiting embodiment, the replay switch assembly 125 includes a "freeze" switch 130 and respective left or  
15 "rewind" and right or "forward" switches 135, 140. Each of these switches 130, 135, 140, in one non-limiting embodiment, are selectively depressible and when selectively depressed generate respective signals to the controller assembly 55 which, upon receipt of these  
20 signals, performs the functions/operations which are delineated below.

The switch 130, when selectively depressed, allows a user to "freeze" or stationarily position a particular portion of the panorama 85 on the display assembly 45.  
25 Once the image or view is "frozen", the user may then use the rewind switch 135 to selectively review previously

displayed and stored image portions of the mosaic or  
panorama 85. The forward switch 140 allows the user to  
rapidly move "forward" or traverse through the previously  
acquired image panoramas and/or mosaics 85 which had  
5 previously be "rewound" or which have been previously  
stored within the memory 35. In one non-limiting  
embodiment, after completely rewinding or forwarding the  
selectively displayed panoramic images 85, the display  
subsystem 45 automatically "freezes" the portion of the  
10 panoramic images 85 being selectively displayed at the  
particular moment in which switch 130 was selectively and  
initially depressed before the "rewinding" or "forwarding"  
occurred. The user may then selectively "zoom in" or  
"zoom out" of the displayed "frozen" portion of the  
15 panorama 85. That is, the user may also selectively  
touch the touch pad 100 and cause the then currently  
displayed image to change from that which represents the  
portion of the environment or ambient environment 83  
which is in close proximity to vehicle 60 to that which  
20 represents the portion of the environment 83 which is  
relatively far from the vehicle 60. Alternatively, the  
distant images may be selectively replaced with close  
images or display assembly 45 may be caused to display  
images of other portions of the ambient environment 83 in  
25 the manner set forth above. The panorama or mosaic 85  
may be acquired, created, and displayed in "real time" by

depressing switch 130 a second time, thereby allowing and/or causing the mosaic 85 to be updated and displayed to the user by display assembly 45 at pre-determined intervals of time.

5       The image control assembly 25 also includes "menu" switches 127. In one embodiment, the first or left switch 140 activates a menu which may be selectively and alphanumerically displayed upon the touch pad 100. Switches 145 selectively allow the user to "scroll" through the presented menu items (i.e., by controlling an electronic pointer which is similar to that used by a computer mouse assembly), while switch 150 selectively allows one of the current or "highlighted" menu options or entries to be selected by a user (i.e., by selectively depressing switch 150 in a manner similar to the depression of a computer mouse switch). The menu switches 127 and the touch pad 100 may also be selectively illuminated by a selectively energizable source of light energy 129 in order to allow these switches 127 and the touch pad 100 to be used in a relatively dark environment.

Control of the display assembly 45 may also be accomplished by the use of a voice activated control assembly 30 which includes a conventional voice recognition interface 131. That is, as best shown in Figure 6, at least one microphone 129 may be selectively

placed within the passenger compartment 53 of vehicle 60 and be adapted to selectively receive sounds from inside of the vehicle 60 and to transmit these received sounds to the voice recognition interface or assembly 131 which  
5 is coupled to controller 55. In one non-limiting embodiment, assembly 131 is selectively programmed to create and transmit certain control signals to the processor assembly 55 in response to the receipt of certain audio information and/or received "sounds". For  
10 example, assembly 131 may be selectively and operatively programmed to send a "freeze" signal to the real time video processing subsystem 55 when the word "stop" is uttered or spoken inside the vehicle 60 by a user and/or operator.

15 Assembly 10 further includes a vehicle control assembly 15 which selectively monitors certain vehicle control attributes and/or functions and which selectively generates and communicates controls signals to the controller 55, effective to cooperatively control the  
20 operation of assembly 10 and the display of the previously acquired image upon display assembly 45. In response to a present sensed "state" or value of one or more of these vehicle control attributes (i.e., engine speed) and/or operations or maneuvers (i.e., placing the  
25 vehicle in "reverse"), the vehicle control subsystem 20 selectively generates and transmits signals to the

controller 55 which are effective to cause the controller 55 to dynamically adjust and/or modify the displayed images 77 in a manner which allows the driver/operator of the vehicle 60 to gain relatively useful visual information.

For example and without limitation, when the vehicle control assembly 20 detects that the driver and/or operator of the vehicle 60 has operatively placed the vehicle shifting lever 141 into the "reverse" position, the vehicle control assembly 20 selectively generates and transmits a signal to the controller 55, effective to selectively cause controller 55 to cause the display of images, objects, regions, and/or areas residing behind the vehicle 60. In this manner, the vehicle driver and/or occupants are able and/or allowed to view the area and/or region which is behind the vehicle 60, thereby gaining visual information of this portion of the ambient environment 83 before the vehicle 60 is selectively moved to and/or within this area and/or region. In response to a sensed engine speed attribute, assembly 15 may automatically cause images from the camera 75 having a field of view 80 in the front of the vehicle 60 to be displayed upon display 45, thereby allowing the driver to gain images of the front of the vehicle 60.

As shown best in Figure 5, assembly 10 further includes a lens cleaning assembly 50 which is selectively

and operatively controlled by the controller 55. That is, should the acquired and/or displayed images, acquired by one or more of the cameras 75, become "unclear" or "hazy", the controller 55 selectively causes assembly 55 to selectively "clean" the protective lens covers 175 which are each respectively seated over a unique one of the lenses of the camera 75 (e.g., each camera 75 is selectively "protected" and/or "covered" by a unique one of the protective lens covers 175).

10 In one non-limiting embodiment, assembly 50 includes an air compressor or pump 180 which is disposed within the vehicle 60 and which selectively generates and releases compressed air. Assembly 50 further includes a container or reservoir 185 which is disposed within the vehicle 60 and which selectively contains a cleansing agent or fluid 187, and a pair of valves 190, 195 which are operatively and selectively coupled, by conduit and/or tube 197, to several nozzles 199 which are each respectively and selectively placed in relative close proximity to a unique one of the lens covers 175 and which are each respectively coupled to pump 180 and to container or reservoir 185. In operation, controller 55 selectively transmits a signal that operatively and selectively opens a first valve 190 while activating pump 180, thereby allowing the generated compressed air to be selectively "blown" or applied to nozzles 199 and to the



lens covers 175. Controller 55 also selectively generates and transmits a second signal effective to open a second valve 195 which allows the cleansing agent 187 to be concomitantly and selectively "blown" or applied upon the lens covers 175 with the compressed air. Once the air and fluid 187 are concomitantly blown onto lenses 175, compressed air is again blown or applied to these covers 175 in order to relatively quickly "dry" the lens covers 175. In the same manner, assembly may also be used to substantially "de-ice" the lens covers 175. Further, in another non-limiting embodiment of the invention, the cleaning agent or liquid 187 (e.g., washer fluid) may be selectively heated using excess engine heat or some other conventional heating method, thereby further allowing assembly 55 to cause ice, which resides upon the lens cover 175, to be relatively quickly melted. The foregoing cleaning procedure may be initiated by receipt of a "cleaning" voice command received by the microphone 129 and assembly 131.

Vehicle data acquisition and display assembly 10 further includes an audio assembly 40 which selectively allows some of the previously acquired or currently acquired data or information (e.g., data representing ambient environment 83) to be selectively and audibly presented to the vehicle driver and/or user. For example and without limitation, assembly 40 selectively announces

the presence of an object which is identified to be in close proximity to the vehicle 60 and which has an image contained within a portion of the mosaic 85. In a further non-limiting embodiment, assembly 40 identifies  
5 the portion or region of the panorama 85 which is selectively presented and displayed by display assembly 45.

It should be understood that this invention is not to be limited to the exact construction or embodiment  
10 described above but that various changes may be made without departing from the spirit or scope of the invention.

**WHAT IS CLAIMED IS:**

(1) A vehicle data acquisition and display assembly comprising:

at least one image acquisition apparatus which is  
5 disposed upon a vehicle and which acquires images of the environment in which said vehicle resides;

a video processing assembly which is coupled to said  
at least one image acquisition apparatus, which receives  
said acquired images, and which uses said acquired images  
10 to create a mosaic image of said environment;

a display which is coupled to said video processing  
assembly, which is disposed within said vehicle, and  
which selectively displays at least one portion of said  
mosaic; and

15 an image control assembly which selects said at least one portion, thereby allowing said at least one portion of said mosaic to be selectively displayed by said display assembly.

(2) The vehicle data acquisition and display assembly of  
20 claim 1 wherein said image acquisition apparatus comprises a camera.

(3) The vehicle data acquisition and display assembly of  
claim 1 wherein said vehicle has at least one attribute  
and wherein said assembly selectively monitors said at  
25 least one attribute and, in response to said monitored attribute, generates a certain signal which is effective

to cause a second portion of said mosaic to be displayed by said display assembly.

(4) The vehicle data acquisition and display assembly of claim 1 wherein said vehicle is selectively maneuvered  
5 and wherein said assembly senses said maneuvering of said vehicle and, in response to said sensed maneuvering, causes a third portion of said mosaic to be displayed by said display assembly.

(5) The vehicle acquisition and display assembly of  
10 claim 4 further comprising a voice activated control assembly which selectively receives at least one voice command and which selectively causes a fourth portion of said mosaic to be displayed in response to said at least one voice command.

15 (6) The vehicle data acquisition and display assembly of claim 1 further comprising:

at least one lens cover; and

a lens cleaning assembly which selectively cleans  
said at least one lens cover.

20 (7) The vehicle data acquisition and display assembly of claim 6 wherein said lens cleaning assembly includes a source of compressed air; and a valve which selectively allows said compressed air to be applied to said at least one lens cover.

25 (8) The vehicle data acquisition and display assembly of claim 7 wherein said lens cleaning assembly further

includes a source of a cleansing agent which is selectively and concomitantly mixed with said applied compressed.

(9) The vehicle data acquisition and display assembly of claim 8 wherein said cleansing agent is warmed before it is mixed with said applied compressed air.

(10) The vehicle data acquisition and display assembly of claim 1 further comprising an audio assembly which selectively generates certain audio signals which describe said at least one portion of said mosaic.

(11) An assembly for use with a vehicle of the type having a roof, said assembly comprising:

a plurality of cameras which are disposed upon said roof and which cooperatively provide images of the environment in which said vehicle resides;

a display assembly which selectively said cooperatively provide images; and

a controller having a touch sensitive surface upon which an icon is disposed, said controller selecting a first portion of said cooperatively provided images by use of said touch sensitive surface and causing said selected first portion of said cooperatively provided images to be displayed by said display assembly.

(12) The assembly of claim 11 wherein each of said cameras have an image acquisition surface which is substantially coplanar with a portion of said roof.

1 (13) The assembly of claim 12 wherein said cooperatively  
provided images include a first image which represents a  
first portion of the environment which is relatively far  
from said vehicle and a second image which represents a  
5 second portion of said environment which is relatively  
close to said vehicle, said controller selecting said  
first image to be displayed upon said display assembly  
when said controller is touched at a point which is  
relatively far from said icon and selecting said second  
10 image to be displayed upon said display assembly when  
said controller is touched at a second point which is  
relatively close to said icon.

(14) The assembly of claim 13 wherein said icon comprises  
an image of a vehicle.

15 (15) The assembly of claim 10 further comprising a voice  
recognition module which causes said first portion of  
said cooperatively provided images to be displayed by  
said display assembly in response to a receipt of a  
certain voice command.

20 (16) The assembly of claim 14 further comprising an audio  
generator which selectively generates certain sounds  
which are based upon said certain portion of said  
cooperatively provided images.

(17) A method for acquiring and selectively displaying  
25 images to be viewed within a vehicle, said method  
comprising the steps of:

providing a plurality of cameras;  
disposing said plurality of cameras upon said  
vehicle, effective to acquire said images;  
providing a display;  
5 disposing said display within said vehicle,  
effective to selectively display at least a portion of  
said images;  
generating a voice command; and  
using said voice command to select said at least a  
10 portion of said images.  
(18) The method of claim 16 further comprising the steps  
of:  
providing a source of air;  
disposing said source of air within said vehicle;  
15 generating a second voice command; and  
causing air to be applied to at least one of said  
plurality of cameras by use of said generated second  
voice command.  
(19) The method of claim 17 wherein each of said cameras  
20 are substantially identical.  
(20) The method of claim 18 further comprising the steps  
of:  
providing a cleansing agent;  
heating said cleansing agent;  
25 mixing said air with said heated cleansing agent;  
and

Study	Year	Age	Sex	Location	Sample Size	Prevalence	95% CI
1	1998	15-64	M	Urban	1000	12.5	8.5-16.5
2	2001	15-64	F	Rural	800	15.2	11.2-19.2
3	2003	15-64	M	Urban	1200	10.8	7.8-13.8
4	2005	15-64	F	Rural	900	14.1	10.1-18.1
5	2007	15-64	M	Urban	1100	11.3	8.3-14.3
6	2009	15-64	F	Rural	950	13.7	9.7-17.7
7	2011	15-64	M	Urban	1050	12.9	9.9-15.9
8	2013	15-64	F	Rural	850	14.5	10.5-18.5
9	2015	15-64	M	Urban	1150	11.7	8.7-14.7
10	2017	15-64	F	Rural	920	13.9	9.9-17.9



### ABSTRACT OF THE DISCLOSURE

A vehicle data acquisition and display assembly 10 which includes several cameras 75 which selectively and cooperatively receive images 77 from the environment or  
5 the ambient environment 83 in which a vehicle 60 resides. The acquired images 77 form a panoramic mosaic 85, at least a portion of which is selectively displayed by a display assembly 45 within the vehicle 60.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32






Figure 1



**Figure 2**



**Figure 3**




Figure 4






Figure 5



## DECLARATION AND POWER OF ATTORNEY - ORIGINAL APPLICATION

Attorney's Docket No.  
199-0680

As a below named inventor, I hereby declare:  
My residence, post office address and citizenship are as stated below next to my name;

I verily believe I am the original, first and sole inventor or an original, first and joint inventor of the subject matter that is claimed and for which a patent is sought on the invention entitled

**VEHICLE DATA ACQUISITION AND DISPLAY ASSEMBLY**

the specification of which is attached hereto.

I have reviewed and understand the contents of the specification identified above, including the claims.

I acknowledge my duty to disclose information of which I am aware that is material to the examination of this application in accordance with Section 1.56(a), Title 37 of the Code of Federal Regulations; and

as to application for patents or inventor's certificate on the invention filed in any country foreign to the United States of America, prior to this application by me or my legal representatives or assigns,

- ☒ no such applications have been filed, or  
☐ such applications have been filed as follows:

COUNTRY	APPLICATION NO.	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Application Number) (Filing Date) (Status - patented, pending, abandoned)

(Application Number) (Filing Date) (Status - patented, pending, abandoned)

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the United States Patent and Trademark Office connected therewith and to act on my behalf before the competent International Authorities in connection with any and all international applications filed by me.

(List name and registration number)

John G. Chupa - 33,483

Mark L. Mollon - 31,123

Mark S. Sparschu - 38,317




Roger L. May - 26,406

**Address all correspondence and telephone calls to:**

John G. Chupa  
Chupa & Alberti, P.C.  
31313 Northwestern Highway, Suite 205  
Farmington Hills, MI 48334

Phone: 1-248-865-9588

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

FULL NAME AND POST OFFICE ADDRESS OF INVENTOR	RESIDENCE	CITIZENSHIP	SIGNATURE	DATE
Vijitha Senaka Kridena 2822 Chaseway Drive Ann Arbor, MI 48105 US	Ann Arbor, MI 48105 US	Sri Lanka		<u>12-7-99</u>
Gregory Hugh Smith 708 West Liberty Street Ann Arbor, MI 48103 US	Ann Arbor, MI 48103 US	U.S.A		<u>12-7-99</u>
Samuel Edward Ebenstein 23020 Coventry Woods Lane Southfield, MI 48034 us	Southfield, MI 48034 US	U.S.A		<u>12-7-99</u>